

1 2 3 4 5 6 7 8

APPEARANCE :

SPECIFICATION

Electrical and Acoustic Characteristics.

Dimensions	25x14x5.2mm
AC Impedance	$8 \pm 15\% \Omega$ at 2000Hz
Rated Input Power	1.0W
Max. input power	1.5W
Resonance Frequency	$700 \pm 20\% \text{Hz}$
Output Sound Pressure Level	$88 \pm 3\text{dB}/0.1\text{M}$ 0.1W at 1.0,1.2,1.5,2.0KHz Average
Frequency Response	Fo~20KHz
Operating Temperature	-20~+65°C
Storage Temperature	-30~+70°C

DIMENSIONS :

FREQUENCY RESPONSE:

<small>UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN MILLIMETER AND (INCHES)</small> <small>DECIMALS .XX ±0.50 (0.02)</small> <small>ANGLES .XXX±0.025 (0.001) ±1°</small> <small>DO NOT SCALE DRAWING</small>	MATERIAL SILICONE RUBBER 60°		TIANER TECHNOLOGY CO., LTD. http://www.itianer.com		
	FINISH BLACK		TITLE		
	DWN BY	DATE	Notebook Speaker		
	CHK BY	DATE	UNIT mm	DWG NO/ PART NO TE-DL1425A-8H5.2	REV 01
THIRD ANGLE PROJEC TION	DESIGN J.M.	DATE '09/08/22	SCALE 5:1	RELEASE DATE 2009/12/23	SHEET

1 2 3 4 5 6 7 8