

1 2 3 4 5 6 7 8

APPEARANCE :

# SPECIFICATION

Electrical and Acoustic Characteristics.

Dimensions	20x3.0mm
AC Impedance	$8 \pm 15\% \Omega$ at 2000Hz
Rated Input Power	2.0W
Max. input power	2.5W
Resonance Frequency	$1000 \pm 20\%$ Hz
Output Sound Pressure Level	$88 \pm 3$ dB/0.1M 0.1W at 0.8,1.0,1.2,1.5KHz Average
Frequency Response	Fo~20KHz
Operating Temperature	-20~+65°C
Storage Temperature	-30~+70°C

DIMENSIONS :

FREQUENCY RESPONSE :

<small>UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN MILLIMETER AND (INCHES)</small> <small>DECIMALS .XX ±0.50 (0.02)</small> <small>.XXX±0.025 (0.001)</small> <small>DO NOT SCALE DRAWING</small> <small>ANGLES (0.02)</small> <small>(0.001) ±1°</small>	MATERIAL	TIANER TECHNOLOGY CO., LTD.		
	SILICONE RUBBER 60°	<a href="http://www.itianer.com">http://www.itianer.com</a>		
	FINISH	TITLE		
	BLACK	Loud Speaker		
THIRD ANGLE PROJECTION	DWN BY	DATE	UNIT	DWG NO/ PART NO
	CHK BY	DATE	mm	TE-DL20B-8H3
	DESIGN	DATE	SCALE	RELEASE DATE
	J.M.	'09/08/22	5:1	2009/12/23
				REV
				01
				SHEET

1 2 3 4 5 6 7 8