

1 2 3 4 5 6 7 8

APPEARANCE :

SPECIFICATION

Electrical and Acoustic Characteristics.

Dimensions	26x5mm
AC Impedance	$8 \pm 15\% \Omega$ at 2000Hz
Rated Input Power	1.2W
Max. input power	1.5W
Resonance Frequency	$600 \pm 20\%$ Hz
Output Sound Pressure Level	92 ± 3 dB/0.1W 0.1m at 0.6,0.8,1.0,1.2KHz Average
Frequency Response	Fo~20KHz
Operating Temperature	-20~+65°C
Storage Temperature	-30~+70°C

DIMENSIONS :

FREQUENCY RESPONSE :

UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN MILLIMETER AND (INCHES) DECIMALS .XX ±0.50 (0.02) .XXX±0.025 (0.001) ±1° DO NOT SCALE DRAWING	MATERIAL SILICONE RUBBER 60°	TIANER TECHNOLOGY CO., LTD. http://www.itianer.com		
	FINISH BLACK	TITLE Mylar Speaker		
THIRD ANGLE PROJECTION	DWN BY	DATE	UNIT mm	DWG NO/ PART NO TE-DM26A-8H5
	CHK BY	DATE	SCALE 5:1	REV 01
	DESIGN J.M.	DATE '09/08/22	RELEASE DATE 2009/12/23	SHEET

1 2 3 4 5 6 7 8